

View Online at <https://aerobasegroup.com/nsn/5915-01-394-8382>

Overall Length:

5.005 inches

Overall Height:

1.920 inches

Body Length:

4.625 inches

Body Width:

2.625 inches

Body Height:

1.600 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.000 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference

Operating Current Rating Per Function In Amps:

3.0 1st radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance-resistance 3rd radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.005 and 0.15 and 0.03 and 0.05 and 0.1 and 0.5 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

1.0 and 7.0 and 15.0 and 22.0 and 35.0 and 60.0 and 60.0 and 60.0 and 60.0 and 60.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded stud

Features Provided:

Moisture resistant and shock resistant

Functional Terminal Type And Quantity:

2 turret input 1st function

Operating Voltage Rating And Type Per Function:

116.0 volts ac 2nd radio interference 2nd function and 232.0 volts dc 1st radio interference 2nd function

Thread Size:

0.138 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

800.0 volts at altitude

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

24.000 ounces

Style Designator:

Rectangular terminal/terminals on two surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0