

View Online at https://aerobasegroup.com/nsn/5915-01-417-2048

Oursell Law of the
Overall Length:
6.200 inches
Body Outside Diameter:
2.270 inches
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
30.0 blank
Mounting Facility Screw Thread Series Designator:
Unef
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity
Functional Terminal Type And Quantity:
1 threaded stud output 2nd function
1 threaded stud output 2nd function
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function:
 1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size:
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material:
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal Style Designator:
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life:
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure:
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization:
1 threaded stud output 2nd function Operating Voltage Rating And Type Per Function: 30.0 volts ac blank and 100.0 volts dc blank Thread Size: 1.125 inches Body Material: Metal Style Designator: Round terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli