

View Online at <https://aerobasegroup.com/nsn/5915-01-466-0893>

Overall Length:

8.620 inches

Overall Height:

4.000 inches

Mounting Slot Width:

0.180 inches

Body Length:

7.000 inches

Body Width:

4.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

7.810 inches

End Application:

Star window airborne system and rct

Source Impedance Rating Per Function:

50.0 cnb ohms per mile

Load Impedance Per Function:

50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

400.0 3rd radio interference

Operating Current Rating Per Function In Amps:

5.0 3rd radio interference

Full Load Insertion Loss Frequencies In Megahertz:

0.02 and 0.05 and 0.15 and 1.5 and 5.0 and 50.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

24.0 and 34.0 and 65.0 and 65.0 and 65.0 and 60.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 slot

Functional Terminal Type And Quantity:

3 threaded stud input 1st function

Operating Voltage Rating And Type Per Function:

125.0 volts ac 1st radio interference 1st function and 250.0 volts ac 1st radio interference 1st function

Special Features:

Low pass emi filter for eliminating power line interference; 3 phase

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0