

View Online at https://aerobasegroup.com/nsn/5915-01-496-1396

Overall Length: 1.250 inches **Body Length:** 0.648 inches **Body Outside Diameter:** 0.410 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank **Power Line Frequency Rating Per Function In Hertz:** 400.0 blank **Operating Current Rating Per Function In Amps:** 1.0 blank Maximum Voltage Drop Per Function: 250.0 millivolts screw on tube not specified and 250.0 millivolts 23rd band suppression not specified **Principal Circuitry Type Per Function:** Capacitance-inductance blank **Maximum Tempurature Rise:** 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unf **Inclosure Type:** Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing **Functional Terminal Type And Quantity:** 1 tab, solder lug output 2nd function **Operating Voltage Rating And Type Per Function:** 125.0 volts ac blank and 200.0 volts dc blank **Thread Size:** 0.250 inches **Body Material:** Metal **Body Surface Treatment:** Tin Style Designator: Round terminal/terminals on opposite surfaces **Test Data Document:** 81349-mil-f-28861 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



Specification Data:

81349-mil-f-28861/5 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0