

View Online at https://aerobasegroup.com/nsn/5915-01-520-5928

Overall Length:
1.067 inches
Body Length:
0.740 inches
Body Outside Diameter:
0.850 inches
Vibration Resistance Range In Hertz:
+10.0/+2000.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Average Life Rating In Hours:
1000.0
End Application:
Counter battery radar (cobra)
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Operating Current Rating Per Function In Amps:
0.60 blank
Maximum Voltage Drop Per Function:
4.2 millivolts dc blank
Principal Circuitry Type Per Function:
Capacitance-inductance blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Functional Terminal Type And Quantity:
1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
28.0 volts dc blank
Thread Size:
0.250 inches
Product Name:
Subminiature filter
Style Designator:
Round terminal/terminals on opposite surfaces



## **Test Data Document:**

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-f-15733/24 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0