

View Online at https://aerobasegroup.com/nsn/5915-01-548-2580

Overall Length:
1.125 inches
Body Length:
0.648 inches
Body Outside Diameter:
0.410 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
1.0 blank
Maximum Voltage Drop Per Function:
250.0 millivolts ac blank and 250.0 millivolts dc blank
Principal Circuitry Type Per Function:
Capacitance-inductance blank
Mounting Facility Screw Thread Series Designator:
Unf
Unf Inclosure Type:
Inclosure Type:
Inclosure Type: Hermetically sealed
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Body Surface Treatment:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Body Surface Treatment: Tin
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Body Surface Treatment: Tin Style Designator:
Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded bushing Functional Terminal Type And Quantity: 1 tab, solder lug input and 1 tab, solder lug output Operating Voltage Rating And Type Per Function: 125.0 volts ac blank and 200.0 volts dc blank Thread Size: 0.250 inches Body Material: Metal Body Surface Treatment: Tin Style Designator: Round terminal/terminals on opposite surfaces

---



Demilitarization:

Yes - demil/mli

Fiig:

A047b0