

View Online at <https://aerobasegroup.com/nsn/5915-01-551-7254>

**Overall Length:**

4.580 inches

**Body Length:**

Between 3.500 inches and 3.620 inches

**Body Outside Diameter:**

1.150 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**End Application:**

Ps degaussing 20, 26, 40kw

**Source Impedance Rating Per Function:**

50.0 tnt any acceptable

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

400.0 blank

**Operating Current Rating Per Function In Amps:**

0.5 blank

**Maximum Voltage Drop Per Function:**

1.25 volts ac blank and 1.25 volts dc blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Functional Terminal Type And Quantity:**

1 tab, solder lug input 1st function and 1 tab, solder lug output 1st function

**Operating Voltage Rating And Type Per Function:**

250.0 volts ac blank 1st function and 600.0 volts dc blank 1st function

**Thread Size:**

0.437 inches

**Body Material:**

Metal

**Product Name:**

Filters, radio frequency interference, style fl56

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Test Data Document:**

81349-mil-prf-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-prf-15733/74a government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0

**Mil-std (military Standard):**

Mil-prf-15733 spec.