

View Online at https://aerobasegroup.com/nsn/5915-01-558-8802

15.200 inches         Overall Height:         4.600 inches         Overall Width:         10.200 inches         Unthreaded Mounting Hole Diameter:         0.472 inches         End Application:         Smart mtr con panel m-300898-a0         Power Line Frequency Rating Per Function In Hertz:         50.0 blank         Operating Current Rating Per Function In Amps:         330.0 blank         Inclosure Type:         Encased         Mounting Facility Type And Quantity:         6 unthreaded hole         Functional Terminal Type And Quantity:         6 date, solder lug input-output 1st function and 2 screw input-output/ground 1st function         Operating Voltage Rating And Type Per Function:         480.0 volts ac blank 1st function         Product Name:         Rifemi filter, three phase, 50/60 hz         Style Designator:         Na         Unit Of Measure:         Na         Unit Of Measure:         To         Pomillarization:         Yes - demil/mill	
Overall Height:         4.600 inches         Overall Width:         10.200 inches         Unthreaded Mounting Hole Diameter:         0.472 inches         End Application:         Smart mtr con panel m-300898-a0         Power Line Frequency Rating Per Function In Hertz:         50.0 blank         Operating Current Rating Per Function In Amps:         330.0 blank         Inclosure Type:         Encased         Mounting Facility Type And Quantity:         6 unthreaded hole         Functional Terminal Type And Quantity:         6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function         Operating Voltage Rating And Type Per Function:         480.0 volts ac blank 1st function         Product Name:         Rifemi filter, three phase, 50/60 hz         Style Designator:         N/a         Unit Of Measure:         r         Pomilitarization:         r         Pomilitarization:         r         Fig:	Overall Length:
4.600 inches         Overall Width:         10.200 inches         Unthreaded Mounting Hole Diameter:         0.472 inches         End Application:         Smart mtr con panel m-300898-a0         Power Line Frequency Rating Per Function In Hertz:         50.0 blank         Operating Current Rating Per Function In Amps:         330.0 blank         Inclosure Type:         Encased         Mounting Facility Type And Quantity:         6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function         Operating Voltage Rating And Type Per Function:         480.0 volts ac blank 1st function         Froduct Name:         Rit/emi filter, three phase, 50/60 hz         Style Designator:         Na         Unit of Measure:         ·         ·         Pointilitarization:         ·         ·         ·         ·         ·         ·         ·         ·         ·         ·         ·         ·         ·         ·         ·         ·	
Overall Width:         10.200 inches         Unthreaded Mounting Hole Diameter:         0.472 inches         End Application:         Smart mtr con panel m-300898-a0         Power Line Frequency Rating Per Function In Hertz:         50.0 blank         Operating Current Rating Per Function In Amps:         330.0 blank         Inclosure Type:         Encased         Mounting Facility Type And Quantity:         6 unthreaded hole         Functional Terminal Type And Quantity:         6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function         Operating Voltage Rating And Type Per Function:         480.0 volts ac blank 1st function         Product Name:         Rectangular terminal/terminals on adjacent surfaces         Shelf Life:         N/a         Unit of Measure:         r         termilitarization:         Yes - demil/mli	-
10.200 inches Unthreaded Mounting Hole Diameter: 0.472 inches End Application: Smart mtr con panel m-300898-a0 Power Line Frequency Rating Per Function In Hertz: 50.0 blank Operating Current Rating Per Function In Amps: 330.0 blank Inclosure Type: Encased Mounting Facility Type And Quantity: 6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rif/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure: - Fig:	
Unthreaded Mounting Hole Diameter: 0.472 inches End Application: Smart mtr con panel m-300898-a0 Power Line Frequency Rating Per Function In Hertz: 50.0 blank Operating Current Rating Per Function In Amps: 330.0 blank Inclosure Type: Encased Mounting Facility Type And Quantity: 6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rif/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli	Overall Width:
0.472 inches         End Application:         Smart mtr con panel m-300898-a0         Power Line Frequency Rating Per Function In Hertz:         50.0 blank         Operating Current Rating Per Function In Amps:         330.0 blank         Inclosure Type:         Encased         Mounting Facility Type And Quantity:         6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function         Operating Voltage Rating And Type Per Function:         480.0 volts ac blank 1st function         Product Name:         Rif/emi filter, three phase, 50/60 hz         Style Designator:         N/a         Unit Of Measure:               Pomilitarization:         Yes - demi/mli	10.200 inches
End Application: Smart mtr con panel m-300898-a0 Power Line Frequency Rating Per Function In Hertz: 50.0 blank Operating Current Rating Per Function In Amps: 330.0 blank Inclosure Type: Encased Mounting Facility Type And Quantity: 6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rif/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli	Unthreaded Mounting Hole Diameter:
Smart mtr con panel m-300898-a0 Power Line Frequency Rating Per Function In Hertz: 50.0 blank Operating Current Rating Per Function In Amps: 330.0 blank Inclosure Type: Encased Mounting Facility Type And Quantity: 6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rif/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Dint Of Measure:  Demilitarization: Yes - demil/mli	0.472 inches
Power Line Frequency Rating Per Function In Hertz:50.0 blankOperating Current Rating Per Function In Amps:330.0 blankInclosure Type:BracsedMounting Facility Type And Quantity:6 unthreaded holeFunctional Terminal Type And Quantity:6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st functionOperating Voltage Rating And Type Per Function:480.0 volts ac blank 1st functionProduct Name:Ridering lifter, three phase, 50/60 hzStyle Designator:NaViaUnit Of Measure:Penilitarization:Yes - demil/mliFig:	End Application:
50.0 blank Operating Current Rating Per Function In Amps: 330.0 blank Inclosure Type: Encased Mounting Facility Type And Quantity: 6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rif/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure: Fmilitarization: Yes - demil/mli	Smart mtr con panel m-300898-a0
Operating Current Rating Per Function In Amps:330.0 blankInclosure Type:EncasedMounting Facility Type And Quantity:6 unthreaded holeFunctional Terminal Type And Quantity:6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st functionOperating Voltage Rating And Type Per Function:480.0 volts ac blank 1st functionProduct Name:Rfi/emi filter, three phase, 50/60 hzStyle Designator:Rectangular terminal/terminals on adjacent surfacesShelf Life:N/aUnit Of Measure:Specification:Yes - demil/mliFiig:	Power Line Frequency Rating Per Function In Hertz:
330.0 blank Inclosure Type: Encased Mounting Facility Type And Quantity: 6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Ri/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli	50.0 blank
Inclosure Type: Encased Mounting Facility Type And Quantity: 6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Ri/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli	Operating Current Rating Per Function In Amps:
Encased Mounting Facility Type And Quantity: 6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rfi/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	330.0 blank
Mounting Facility Type And Quantity:6 unthreaded holeFunctional Terminal Type And Quantity:6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st functionOperating Voltage Rating And Type Per Function:480.0 volts ac blank 1st functionProduct Name:Rfi/emi filter, three phase, 50/60 hzStyle Designator:Rectangular terminal/terminals on adjacent surfacesShelf Life:Init Of Measure:Demilitarization:Yes - demil/mliFiig:	Inclosure Type:
6 unthreaded hole Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rfi/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Encased
Functional Terminal Type And Quantity: 6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rti/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Mounting Facility Type And Quantity:
6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rfi/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	6 unthreaded hole
Operating Voltage Rating And Type Per Function: 480.0 volts ac blank 1st function Product Name: Rfi/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Functional Terminal Type And Quantity:
480.0 volts ac blank 1st function Product Name: Rfi/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	6 tab, solder lug input-output 1st function and 2 screw input-output/ground 1st function
Product Name: Rfi/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Operating Voltage Rating And Type Per Function:
Rfi/emi filter, three phase, 50/60 hz Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	480.0 volts ac blank 1st function
Style Designator: Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Product Name:
Rectangular terminal/terminals on adjacent surfaces Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Rfi/emi filter, three phase, 50/60 hz
Shelf Life: N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Style Designator:
N/a Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Rectangular terminal/terminals on adjacent surfaces
Unit Of Measure:  Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
 Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
-	Yes - demil/mli
	Fiig:
A047b0	A047b0