

View Online at <https://aerobasegroup.com/nsn/5915-01-571-3042>

**Overall Length:**

0.502 inches

**Body Length:**

0.170 inches

**Body Outside Diameter:**

0.385 inches

**Operating Current Rating Per Function In Amps:**

15.0 blank

**Maximum Voltage Drop Per Function:**

0.15 volts dc blank

**Full Load Insertion Loss Frequencies In Megahertz:**

0.030 and 0.15 and 0.30 and 1.00 and 10.00 and 10000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

15.0 and 28.0 and 33.0 and 44.0 and 60.0 and 70.0 and 70.0

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Operating Voltage Rating And Type Per Function:**

50.0 volts dc blank

**Thread Size:**

0.250 inches

**Special Features:**

500 degrees f soldering temperature; 8 lb-ins. torque; tin plated steel bushing, solder plated copper lead, tin plated brass nut and tin plated phosphor bronze I washer

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0