

View Online at <https://aerobasegroup.com/nsn/5915-01-571-3042>

Overall Length:

0.502 inches

Body Length:

0.170 inches

Body Outside Diameter:

0.385 inches

Operating Current Rating Per Function In Amps:

15.0 blank

Maximum Voltage Drop Per Function:

0.15 volts dc blank

Full Load Insertion Loss Frequencies In Megahertz:

0.030 and 0.15 and 0.30 and 1.00 and 10.00 and 10000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

15.0 and 28.0 and 33.0 and 44.0 and 60.0 and 70.0 and 70.0

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

1 threaded bushing

Operating Voltage Rating And Type Per Function:

50.0 volts dc blank

Thread Size:

0.250 inches

Special Features:

500 degrees f soldering temperature; 8 lb-ins. torque; tin plated steel bushing, solder plated copper lead, tin plated brass nut and tin plated phosphor bronze I washer

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0