## NSN 5915-01-612-6899

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-612-6899

**Overall Length:** 

1.062 inches

**Mounting Slot Width:** 

Between 0.100 inches and 0.125 inches

**Body Outside Diameter:** 

0.410 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.060 inches and 0.080 inches

**Operating Tempurature Range:** 

-55.0 to 125.0 degrees celsius

**End Application:** 

4920-01-495-8100

**Operating Current Rating Per Function In Amps:** 

0.1 blank single function

**Maximum Voltage Drop Per Function:** 

0.17 volts dc blank single function

**Maximum Tempurature Rise:** 

25.0 degrees celsius

**Mounting Facility Screw Thread Series Designator:** 

Unf

**Inclosure Type:** 

Hermetically sealed

**Mounting Facility Type And Quantity:** 

2 unthreaded hole single function

**Functional Terminal Type And Quantity:** 

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:** 

70.0 volts dc blank single function

Thread Size:

0.250 inches

**Body Material:** 

Metal

**Body Surface Treatment:** 

Tin

**Product Name:** 

Subminature filters

**Special Features:** 

Pure tin finish treatment is prohibited

**Unpackaged Unit Weight:** 

10.0 grams

**Style Designator:** 

Round terminal/terminals on opposite surfaces

## NSN 5915-01-612-6899

Radio Frequency Interference Filter - Page 2 of 2



Specification Data:
81349/mil-prf-28861/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A047b0
Mil-std (military Standard):

Mil-prf-28861 spec.