## NSN 5920-00-009-6812



| Cartridge Fuse - Page 1 of 1  |            |
|---|------------|
| View Online at https://aerobasegroup.com/nsn/5920-00-009-6812   |            |
| Body Style:   |            |
| Tube type   |            |
| Terminal Surface Treatment:   |            |
| Silver plated   |            |
| Overall Length:   |            |
| 1.250 inches  |            |
| Overall Diameter:   |            |
| 0.250 inches  |            |
| Continuous Current Rating In Amps:  |            |
| 1.000   |            |
| Maximum Voltage Rating In Volts:  |            |
| 250.0 ac and 250.0 dc   |            |
| Circuit Over-current Interruption Type:   |            |
| Normal instantaneous  |            |
| Interruption Indicator Method:  |            |
| Visible element   |            |
| Features Provided:  |            |
| Nonrenewable fusible element  |            |
| Criticality Code Justification:   |            |
| Feat  |            |
| Short-circuit/interrupt Current Rating In Amps:   |            |
| 35.0  |            |
| Special Features:   |            |
| Item must comply with requirements of desc production standard no. L00258, for navy nuclear propulsion plant production | ducts only |
| Precious Material And Location:   |            |
| Terminal surfaces silver  |            |
| Precious Material:  |            |
| Silver  |            |
| Shelf Life:   |            |
| N/a   |            |
| Unit Of Measure:  |            |
|   |            |
| Demilitarization:   |            |
| No  |            |
| Fiig:   |            |
| A01700  |            |
|   |            |
|   |            |
|   |            |
|   |            |