

View Online at <https://aerobasegroup.com/nsn/5920-00-018-1450>

Body Material:

Plastic, phenolic, mil-m-14, type cfg

Body Style:

Bushing mounted type

Terminal Material:

Brass

Terminal Surface Treatment:

Tin plated

Overall Length:

Between 1.745 inches and 1.755 inches

Bushing Diameter:

0.500 inches

Overall Width:

Between 0.615 inches and 0.635 inches

Body Diameter:

Between 0.680 inches and 0.690 inches

Mounting Hole Quantity:

1

Environmental Protection:

Vibration proof

Mounting Hole Style:

Bushing mounting

Contact Material:

Brass

Contact Surface Treatment:

Tin plated

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

Between 0.724 inches and 0.744 inches

Bushing Thread Length:

Between 1.006 inches and 1.026 inches

Cap Diameter:

Between 0.680 inches and 0.690 inches

Bushing Hole Diameter:

Between 0.502 inches and 0.510 inches

Flatted Side Bushing Hole Length:

Between 0.475 inches and 0.480 inches

Current Carrying Rating In Amps:

15.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Test Data Document:

96214-412723-1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0