

View Online at <https://aerobasegroup.com/nsn/5920-00-053-8958>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Panel mounted type

Overall Length:

Between 3.750 inches and 4.000 inches

Overall Height:

Between 1.812 inches and 1.817 inches

Overall Width:

Between 1.180 inches and 1.185 inches

Mounting Hole Diameter:

Between 0.151 inches and 0.161 inches

Mounting Hole Quantity:

2

Environmental Protection:

Dripproof

Mounting Hole Style:

2 bushing mounting w/2 holes

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

330.0 ohms

Indicating Lamp Voltage Range In Volts:

+23.0/+33.0

Length From Front Protrusion To Mounting Surface:

Between 0.798 inches and 0.828 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.933 inches and 0.943 inches

Bushing Hole Diameter:

Between 0.869 inches and 0.879 inches

Center To Center Distance Between Bushing Holes:

Between 0.795 inches and 0.805 inches

Center To Center Distance Between Keyway And Bushing Hole:

Between 0.464 inches and 0.474 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Test Data Document:

81349-mil-f-19207/18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0