

View Online at <https://aerobasegroup.com/nsn/5920-00-061-3355>

**Body Material:**

Plastic, glass fiber, reinforced

**Body Style:**

Bushing mounted type

**Overall Length:**

2.625 inches

**Bushing Diameter:**

0.875 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

0.875 inches

**Environmental Protection:**

Splash proof

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Brass

**Contact Surface Treatment:**

Nickel plated

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

0.625 inches

**Bushing Thread Length:**

1.500 inches

**Bushing Hole Diameter:**

Between 0.875 inches and 0.879 inches

**Flatted Side Bushing Hole Length:**

Between 0.750 inches and 0.800 inches

**Screw Thread Diameter:**

0.138 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0