

View Online at <https://aerobasegroup.com/nsn/5920-00-061-7123>

Body Style:

Tube type

Terminal Material:

Brass

Terminal Surface Treatment:

Nickel

Overall Length:

Between 1.969 inches and 2.031 inches

Overall Diameter:

Between 0.556 inches and 0.568 inches

Case Material:

Fiber

Continuous Current Rating In Amps:

25.000

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Circuit Over-current Interruption Type:

Time delay

Interruption Indicator Method:

Opaque body

Features Provided:

Nonrenewable fusible element

Circuit Over-current Interruption Delay Time In Seconds:

10.0 400 pct of current rating

Short-circuit/interrupt Current Rating In Amps:

10000.0

Test Data Document:

81349-mil-prf-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-15160/15 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A01700

Mil-std (military Standard):

Mil-prf-15160 spec.