## NSN 5920-00-065-1736

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-00-065-1736

Body Style: Tube type Terminal Material: Brass Overall Length: 1.500 inches Overall Diameter: 0.406 inches Case Material: Plastic, melamine, glass filled Continuous Current Rating In Amps: 2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Terminal Material: Brass Overall Length: 1.500 inches Overall Diameter: 0.406 inches Case Material: Plastic, melamine, glass filled Continuous Current Rating In Amps: 2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Brass Overall Length: 1.500 inches Overall Diameter: 0.406 inches Case Material: Plastic, melamine, glass filled Continuous Current Rating In Amps: 2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Overall Length:1.500 inchesOverall Diameter:0.406 inchesCase Material:Plastic, melamine, glass filledContinuous Current Rating In Amps:2.000Maximum Voltage Rating In Volts:600.0 acCircuit Over-current Interruption Type:Normal instantaneousInterruption Indicator Method:Opaque bodyFeatures Provided:Nonrenewable fusible element
<ul> <li>1.500 inches</li> <li>Overall Diameter:</li> <li>0.406 inches</li> <li>Case Material:</li> <li>Plastic, melamine, glass filled</li> <li>Continuous Current Rating In Amps:</li> <li>2.000</li> <li>Maximum Voltage Rating In Volts:</li> <li>600.0 ac</li> <li>Circuit Over-current Interruption Type:</li> <li>Normal instantaneous</li> <li>Interruption Indicator Method:</li> <li>Opaque body</li> <li>Features Provided:</li> <li>Nonrenewable fusible element</li> </ul>
Overall Diameter: 0.406 inches Case Material: Plastic, melamine, glass filled Continuous Current Rating In Amps: 2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
0.406 inches Case Material: Plastic, melamine, glass filled Continuous Current Rating In Amps: 2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Case Material: Plastic, melamine, glass filled Continuous Current Rating In Amps: 2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Plastic, melamine, glass filled Continuous Current Rating In Amps: 2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Continuous Current Rating In Amps: 2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
2.000 Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Maximum Voltage Rating In Volts: 600.0 ac Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
600.0 ac <b>Circuit Over-current Interruption Type:</b> Normal instantaneous <b>Interruption Indicator Method:</b> Opaque body <b>Features Provided:</b> Nonrenewable fusible element
Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Normal instantaneous Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Interruption Indicator Method: Opaque body Features Provided: Nonrenewable fusible element
Opaque body Features Provided: Nonrenewable fusible element
Features Provided: Nonrenewable fusible element
Nonrenewable fusible element
Object sinestificterment Operand Define In America
Short-circuit/interrupt Current Rating In Amps:
100000.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A01700