NSN 5920-00-121-5509

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-121-5509 **Body Material:** Plastic, diallyl phthalate, mil-m-14, type sdg **Body Style:** Bushing mounted type **Terminal Surface Treatment:** Solder dip **Overall Length:** 2.812 inches **Bushing Diameter:** 0.625 inches **Body Diameter:** 0.812 inches **Mounting Hole Quantity: Overall Diameter:** 0.812 inches **Environmental Protection:** Dripproof **Mounting Hole Style: Bushing mounting Contact Material:** Any acceptable **Contact Surface Treatment:** Any acceptable **Interruption Indicator Method:** Neon lamp **Fuse Accommodation Quantity: Accommodated Fuse Length:** 1.250 inches **Accommodated Ferrule Diameter:** 0.250 inches **Resistor Rating:** 220.0 kilohms **Indicating Lamp Voltage Range In Volts:** +90.0/+250.0 **Length From Front Protrusion To Mounting Surface:** 1.188 inches **Bushing Thread Length:**

Bushing Hole Diameter:

Between 0.625 inches and 0.635 inches

0.438 inches

NSN 5920-00-121-5509

A014a0

Extractor Post Fuseholder - Page 2 of 2



Flatted Side Bushing Hole Length:
Between 0.585 inches and 0.595 inches
Current Carrying Rating In Amps:
15.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
250.0
Special Features:
Fungus resistant, 200 hrs salt spray test, terminals solder dipped before assembly
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: