

View Online at <https://aerobasegroup.com/nsn/5920-00-122-0334>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type sdg

**Body Style:**

Bushing mounted type

**Terminal Material:**

Copper

**Terminal Surface Treatment:**

Solder dip

**Overall Length:**

3.281 inches

**Bushing Diameter:**

0.625 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

0.812 inches

**Environmental Protection:**

Fungus proof and dripproof

**Mounting Hole Style:**

Bushing mounting

**Lens Color:**

Amber

**Contact Material:**

Brass

**Contact Surface Treatment:**

Any acceptable

**Interruption Indicator Method:**

Incandescent lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

330.0 ohms

**Indicating Lamp Voltage Range In Volts:**

+22.0 to 33.0

**Length From Front Protrusion To Mounting Surface:**

1.188 inches

**Bushing Thread Length:**

0.500 inches

**Cap Diameter:**

0.688 inches

**Bushing Hole Diameter:**

Between 0.625 inches and 0.635 inches

**Flatted Side Bushing Hole Length:**

Between 0.585 inches and 0.595 inches

**Current Carrying Rating In Amps:**

20.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

33.0

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0