## NSN 5920-00-131-9842

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-131-9842

Body Style: Axial terminal type Terminal Material: Brass Terminal Surface Treatment: Silver plated Overall Length: 4.375 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.625 inches Mounting Slot Width: 0.312 inches Body Length: 2.750 inches Overall Diameter: 1.062 inches Case Material: Fiber Continuous Current Rating In Amps: 175.000 Terminal Width: 0.688 inches Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc
Terminal Material: Brass  Terminal Surface Treatment: Silver plated  Overall Length: 4.375 inches  Center To Center Distance Between Mounting Facilities Parallel To Length: 3.625 inches  Mounting Slot Width: 0.312 inches  Body Length: 2.750 inches  Overall Diameter: 1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Brass Terminal Surface Treatment: Silver plated Overall Length: 4.375 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.625 inches Mounting Slot Width: 0.312 inches Body Length: 2.750 inches Overall Diameter: 1.062 inches Case Material: Fiber Continuous Current Rating In Amps: 175.000 Terminal Width: 0.688 inches Maximum Voltage Rating In Volts:
Terminal Surface Treatment: Silver plated Overall Length: 4.375 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.625 inches Mounting Slot Width: 0.312 inches Body Length: 2.750 inches Overall Diameter: 1.062 inches Case Material: Fiber Continuous Current Rating In Amps: 175.000 Terminal Width: 0.688 inches Maximum Voltage Rating In Volts:
Silver plated  Overall Length: 4.375 inches  Center To Center Distance Between Mounting Facilities Parallel To Length: 3.625 inches  Mounting Slot Width: 0.312 inches  Body Length: 2.750 inches  Overall Diameter: 1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Overall Length: 4.375 inches  Center To Center Distance Between Mounting Facilities Parallel To Length: 3.625 inches  Mounting Slot Width: 0.312 inches  Body Length: 2.750 inches  Overall Diameter: 1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
4.375 inches  Center To Center Distance Between Mounting Facilities Parallel To Length: 3.625 inches  Mounting Slot Width: 0.312 inches  Body Length: 2.750 inches  Overall Diameter: 1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Center To Center Distance Between Mounting Facilities Parallel To Length: 3.625 inches  Mounting Slot Width: 0.312 inches  Body Length: 2.750 inches  Overall Diameter: 1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Mounting Slot Width:  0.312 inches  Body Length: 2.750 inches  Overall Diameter: 1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Mounting Slot Width:  0.312 inches  Body Length:  2.750 inches  Overall Diameter:  1.062 inches  Case Material:  Fiber  Continuous Current Rating In Amps:  175.000  Terminal Width:  0.688 inches  Maximum Voltage Rating In Volts:
0.312 inches  Body Length: 2.750 inches  Overall Diameter: 1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Body Length:  2.750 inches  Overall Diameter:  1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps:  175.000  Terminal Width:  0.688 inches  Maximum Voltage Rating In Volts:
2.750 inches  Overall Diameter: 1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Overall Diameter:  1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps:  175.000  Terminal Width:  0.688 inches  Maximum Voltage Rating In Volts:
1.062 inches  Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Case Material: Fiber  Continuous Current Rating In Amps: 175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Fiber  Continuous Current Rating In Amps:  175.000  Terminal Width:  0.688 inches  Maximum Voltage Rating In Volts:
Continuous Current Rating In Amps: 175.000 Terminal Width: 0.688 inches Maximum Voltage Rating In Volts:
175.000  Terminal Width: 0.688 inches  Maximum Voltage Rating In Volts:
Terminal Width:  0.688 inches  Maximum Voltage Rating In Volts:
0.688 inches  Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts:
125.0 ac and 125.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
13.0 500 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
500.0
Precious Material And Location:
Terminal surfaces silver
Precious Material:
Precious Material: Silver
Silver

## NSN 5920-00-131-9842

Cartridge Fuse - Page 2 of 2



Demilitarization:

No

Fiig:

A01700