

View Online at <https://aerobasegroup.com/nsn/5920-00-132-6429>

**Body Style:**

Panel mounted type

**Overall Length:**

3.875 inches

**Overall Height:**

1.812 inches

**Overall Width:**

1.188 inches

**Mounting Hole Diameter:**

0.156 inches

**Mounting Hole Quantity:**

2

**Environmental Protection:**

Any acceptable

**Mounting Hole Style:**

2 bushing mounting w/2 holes

**Lens Color:**

Clear

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Nickel plated

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

2

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

120.0 kilohms

**Length From Front Protrusion To Mounting Surface:**

0.812 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

0.938 inches

**Bushing Hole Diameter:**

0.875 inches

**Center To Center Distance Between Bushing Holes:**

0.800 inches

**Center To Center Distance Between Keyway And Bushing Hole:**

0.469 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Criticality Code Justification:**

Feat

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L00113. For navy nuclear propulsion plant

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0