

View Online at <https://aerobasegroup.com/nsn/5920-00-162-2218>

**Body Style:**

Shielded-bushing mounted type

**Overall Length:**

2.672 inches

**Bushing Diameter:**

0.500 inches

**Mounting Hole Quantity:**

1

**Body Length:**

2.500 inches

**Overall Diameter:**

0.875 inches

**Environmental Protection:**

Shock proof

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Brass

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

1.000 inches

**Bushing Thread Length:**

0.500 inches

**Cap Diameter:**

0.812 inches

**Bushing Hole Diameter:**

Between 0.500 inches and 0.510 inches

**Flatted Side Bushing Hole Length:**

Between 0.468 inches and 0.478 inches

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Precious Material And Location:**

Contact surface silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0