

View Online at <https://aerobasegroup.com/nsn/5920-00-170-4226>

**Body Style:**

Rear panel mounted type

**Overall Length:**

3.875 inches

**Overall Height:**

Between 1.200 inches and 1.205 inches

**Overall Width:**

Between 1.068 inches and 1.072 inches

**Keyway Width:**

0.200 inches

**Mounting Hole Diameter:**

0.156 inches

**Mounting Hole Quantity:**

2

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting w/2 holes and keyway

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Any acceptable

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

120.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+90.0 to 250.0

**Length From Front Protrusion To Mounting Surface:**

Between 0.798 inches and 0.828 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

0.750 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

0.875 inches

**Bushing Hole Diameter:**

0.875 inches

**Center To Center Distance Between Keyway And Bushing Hole:**

0.437 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Criticality Code Justification:**

Feat

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Special Features:**

Item must comply w/rqmts of desc production standard no. L00026

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0