## NSN 5920-00-172-1431

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-172-1431 **Body Style:** Panel mounted type **Overall Length:** 3.875 inches **Overall Height:** Between 1.812 inches and 1.817 inches Overall Width: Between 1.180 inches and 1.185 inches **Mounting Hole Diameter:** 0.156 inches **Mounting Hole Quantity: Environmental Protection:** Dripproof **Mounting Hole Style:** 2 bushing mounting w/2 holes **Contact Material:** Copper **Contact Surface Treatment:** Any acceptable **Interruption Indicator Method:** Incandescent lamp **Fuse Accommodation Quantity: Accommodated Fuse Length:** 1.250 inches **Accommodated Ferrule Diameter:** 0.250 inches **Resistor Rating:** 330.0 ohms **Length From Front Protrusion To Mounting Surface:** 0.813 inches **Center To Center Distance Between Outside Mounting Holes Along Width:** 0.938 inches **Bushing Hole Diameter:** 0.874 inches **Center To Center Distance Between Bushing Holes:** 0.800 inches Center To Center Distance Between Keyway And Bushing Hole:

0.469 inches

**Screw Thread Diameter:** 

0.164 inches

## NSN 5920-00-172-1431

Extractor Post Fuseholder - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Criticality Code Justification:
Feat
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
33.0
Special Features:
Item must comply w/rqmts of desc production standard no. L00578
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A014a0