# NSN 5920-00-179-4580

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-179-4580

## **Body Material:**

Plastic, polyester, mil-m-14, type mai-60

Body Style:

Panel mounted type

## **Overall Length:**

2.000 inches

## **Overall Height:**

1.810 inches

## **Overall Width:**

2.090 inches

## Mounting Hole Diameter:

0.138 inches

## Mounting Hole Quantity:

1

#### Panel Thickness:

#### 0.187 inches

Environmental Protection:

Watertight

#### Mounting Hole Style:

Panel mounting w/2 or 3 holes

Contact Material:

#### Any acceptable

#### **Contact Surface Treatment:**

Any acceptable

#### Interruption Indicator Method:

Neon lamp

#### **Fuse Accommodation Quantity:**

2

#### Accommodated Fuse Length:

1.250 inches

## Accommodated Ferrule Diameter:

0.250 inches

## **Resistor Rating:**

120.0 kilohms

# Length From Front Protrusion To Mounting Surface:

0.873 inches

## Cap Diameter:

0.625 inches

## Mounting Hole Height:

1.594 inches

# Mounting Hole Width:

1.375 inches

Extractor Post Fuseholder - Page 2 of 2



#### Center To Center Distance Between Outside Mounting Holes Along Length:

1.780 inches

#### Center To Center Distance Between Outside Mounting Holes Along Width:

0.880 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

**Current Carrying Rating In Amps:** 

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

**Precious Material And Location:** 

Contact surfaces silver

**Precious Material:** 

Silver

#### Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-f-19207/22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 threaded stud Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A014a0