## NSN 5920-00-199-4022

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-00-199-4022 **Body Style:** Tube type **Terminal Material:** Brass or copper or copper alloy **Terminal Surface Treatment:** Nickel **Overall Length:** Between 1.469 inches and 1.531 inches **Overall Diameter:** Between 0.402 inches and 0.410 inches **Case Material:** Fiber **Continuous Current Rating In Amps:** 8.000 **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Opaque body **Features Provided:** Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 12.0 200 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 100.0

Test Data Document:

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-f-15160/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A01700