## NSN 5920-00-203-5938

Cartridge Fuse - Page 1 of 1

No Fiig: A01700



View Online at https://aerobasegroup.com/nsn/5920-00-203-5938 **Body Style:** Self indicating type **Terminal Surface Treatment:** Nickel **Overall Length:** Between 1.234 inches and 1.296 inches **Body Length:** 1.187 inches **Overall Diameter:** Between 0.290 inches and 0.310 inches **Continuous Current Rating In Amps:** 8.000 **Maximum Voltage Rating In Volts:** 125.0 ac and 125.0 dc **Circuit Over-current Interruption Type:** Normal instantaneous **Interruption Indicator Method:** Terminal-visual or alarm **Features Provided:** Nonrenewable fusible element **Short-circuit/interrupt Current Rating In Amps:** 1000.0 **Special Features:** Cage 71400, type code f distributor, cooper bussmann, Ilc, 114 old state rd. Ellisville, mo 63021-5915, ph. 636-527-1317: per 339 (dscc-fm-14-88416) cooper bussmann (71400), now eaton, is the largest manufacturer of fuses and circuit breakers in 5920 stock class. **Test Data Document:** 81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-f-15160/77 government specification Shelf Life: N/a **Unit Of Measure:** Demilitarization: