

View Online at <https://aerobasegroup.com/nsn/5920-00-204-8110>

Body Style:

Rear panel mounted type

Overall Length:

3.875 inches

Overall Height:

Between 1.200 inches and 1.205 inches

Overall Width:

1.070 inches

Keyway Width:

0.205 inches

Mounting Hole Diameter:

0.156 inches

Mounting Hole Quantity:

2

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting w/2 holes and keyway

Lens Color:

Amber

Contact Material:

Copper

Contact Surface Treatment:

Any acceptable

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

1.8 kilohms

Indicating Lamp Voltage Range In Volts:

+61.0/+80.0

Length From Front Protrusion To Mounting Surface:

0.813 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

0.750 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.875 inches

Bushing Hole Diameter:

0.875 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.437 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Criticality Code Justification:

Feat

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

80.0

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. Lo119. For navy nuclear propulsion plant products only

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0