Extractor Post Fuseholder - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-00-221-5668

| | verall Length: |
|-----|---------------------------------|
| | 141 inches |
| | ushing Diameter: |
| | 500 inches |
| | verall Diameter: |
| | 688 inches |
| | nvironmental Protection: |
| | ny acceptable |
| Сс | ontact Material: |
| | ass or copper |
| Co | ontact Surface Treatment: |
| Ar | ny acceptable |
| In | terruption Indicator Method: |
| Τe | est hole |
| Fι | use Accommodation Quantity: |
| 1 | |
| Ac | ccommodated Fuse Length: |
| 1.2 | 250 inches |
| Ac | ccommodated Ferrule Diameter: |
| 0.2 | 250 inches |
| Вι | ushing Thread Length: |
| 0. | 500 inches |
| Сι | urrent Carrying Rating In Amps: |
| 15 | 5.0 |
| Fι | use Terminal Type Accommodated: |
| Fe | errule |
| Vc | oltage In Volts: |
| 25 | 50.0 |
| Те | erminal Type And Quantity: |
| 21 | tab, solder lug |
| Sł | nelf Life: |
| N/ | 'a |
| Ur | nit Of Measure: |
| | |
| De | emilitarization: |
| No | |
| Fi | ig: |
| | 014a0 |