

View Online at <https://aerobasegroup.com/nsn/5920-00-280-3175>

**Body Style:**

Tube type

**Terminal Material:**

Brass

**Terminal Surface Treatment:**

Nickel

**Overall Length:**

Between 1.469 inches and 1.531 inches

**Overall Diameter:**

Between 0.402 inches and 0.410 inches

**Case Material:**

Fiber

**Continuous Current Rating In Amps:**

1.600

**Maximum Voltage Rating In Volts:**

125.0 ac and 125.0 dc

**Circuit Over-current Interruption Type:**

Time delay

**Interruption Indicator Method:**

Opaque body

**Features Provided:**

Nonrenewable fusible element

**Circuit Over-current Interruption Delay Time In Seconds:**

3.0 500 pct of current rating

**Short-circuit/interrupt Current Rating In Amps:**

10000.0

**Test Data Document:**

81349-mil-prf-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-prf-15160/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A01700

**Mil-std (military Standard):**

Mil-prf-15160 spec.