NSN 5920-00-280-5038



Cartridge Fuse - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5920-00-280-5038 **Body Style:** Tube type **Terminal Material:** Brass or copper or copper alloy **Terminal Surface Treatment:** Silver plated **Overall Length:** Between 1.219 inches and 1.281 inches **Overall Diameter:** Between 0.246 inches and 0.254 inches Case Material: Plastic or ceramic **Continuous Current Rating In Amps:** 0.500 **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Opaque body **Features Provided:** Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 12.0 200 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 35.0 **Precious Material And Location:** Terminal surfaces silver **Precious Material:** Silver **Test Data Document:** 81349-mil-prf-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-prf-15160/3 government specification Shelf Life: N/a **Unit Of Measure:**

Fiig: A01700

No

Demilitarization:

NSN 5920-00-280-5038

Cartridge Fuse - Page 2 of 2



Mil-std (military Standard):

Mil-prf-15160 spec.