

View Online at <https://aerobasegroup.com/nsn/5920-00-280-9348>

**Body Style:**

Tangent terminal type

**Terminal Material:**

Brass

**Terminal Surface Treatment:**

Nickel

**Overall Length:**

Between 1.719 inches and 1.781 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.969 inches and 1.031 inches

**Overall Width:**

Between 1.281 inches and 1.343 inches

**Mounting Slot Width:**

Between 0.259 inches and 0.260 inches

**Overall Diameter:**

Between 0.781 inches and 0.843 inches

**Case Material:**

Fiber

**Continuous Current Rating In Amps:**

50.000

**Terminal Thickness:**

0.047 inches

**Maximum Voltage Rating In Volts:**

32.0 ac and 32.0 dc

**Circuit Over-current Interruption Type:**

Time delay

**Interruption Indicator Method:**

Opaque body

**Features Provided:**

Nonrenewable fusible element

**Circuit Over-current Interruption Delay Time In Seconds:**

15.0 300 pct of current rating

**Short-circuit/interrupt Current Rating In Amps:**

10000.0

**Test Data Document:**

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-f-15160/40 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A01700