NSN 5920-00-280-9348

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-280-9348

Body Style:

Tangent terminal type

Terminal Material:

Brass

Terminal Surface Treatment:

Nickel

Overall Length:

Between 1.719 inches and 1.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.969 inches and 1.031 inches

Overall Width:

Between 1.281 inches and 1.343 inches

Mounting Slot Width:

Between 0.259 inches and 0.260 inches

Overall Diameter:

Between 0.781 inches and 0.843 inches

Case Material:

Fiber

Continuous Current Rating In Amps:

50.000

Terminal Thickness:

0.047 inches

Maximum Voltage Rating In Volts:

32.0 ac and 32.0 dc

Circuit Over-current Interruption Type:

Time delay

Interruption Indicator Method:

Opaque body

Features Provided:

Nonrenewable fusible element

Circuit Over-current Interruption Delay Time In Seconds:

15.0 300 pct of current rating

Short-circuit/interrupt Current Rating In Amps:

10000.0

Test Data Document:

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15160/40 government specification

Shelf Life:

N/a

Unit Of Measure:

NSN 5920-00-280-9348

Cartridge Fuse - Page 2 of 2

Demilitarization:

No

Fiig:

A01700

