## NSN 5920-00-281-0162

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-281-0162

Body Style:
Knife blade type
Terminal Material:
Copper
Terminal Surface Treatment:
Nickel
Overall Length:
Between 5.812 inches and 5.937 inches
Terminal Length:
1.000 inches
Overall Diameter:
1.312 inches
Case Material:
Fiber
Continuous Current Rating In Amps:
100.000
Terminal Width:
Between 0.715 inches and 0.785 inches
Terminal Thickness:
Between 0.122 inches and 0.128 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
10.0 500 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
10000.0
Test Data Document:
81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-f-15160/19 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## **NSN 5920-00-281-0162**Cartridge Fuse - Page 2 of 2



Fiig:

A01700