

View Online at <https://aerobasegroup.com/nsn/5920-00-284-6787>

Body Style:

Tube type

Terminal Surface Treatment:

Nickel

Overall Length:

1.250 inches

Overall Diameter:

0.250 inches

Continuous Current Rating In Amps:

5.000

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Circuit Over-current Interruption Type:

Normal instantaneous

Interruption Indicator Method:

Visible element

End Application:

Navstar global positioning system user equipment (ue); systems, 02n2; skupport equipment, b-52 aircraft; communications terminal, satellite (an/tsc-94); missile, advanced medium range air-to-air (amraam) aim120a; radar set, an/tpn-18; countermeasure set, an/slq-32; support equipment, b-1 aircraft; fire pumps; an/spn-35b

Features Provided:

Nonrenewable fusible element

Short-circuit/interrupt Current Rating In Amps:

100.0

Test Data Document:

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15160/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A01700