## NSN 5920-00-295-9704

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-00-295-9704

view Offiline at https://aerobasegroup.com/nish/5525-50-235-3704
Body Style:
Tube type
Terminal Material:
Brass or copper or copper alloy
Terminal Surface Treatment:
Silver plated
Overall Length:
Between 1.469 inches and 1.531 inches
Overall Diameter:
Between 0.402 inches and 0.410 inches
Case Material:
Fiber
Continuous Current Rating In Amps:
0.500
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
12.0 200 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
35.0
Precious Material And Location:
Terminal surfaces silver
Precious Material:
Silver
Test Data Document:
81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-f-15160/9 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No

A01700

Fiig: