## NSN 5920-00-296-2239

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-296-2239 **Body Style:** Panel mounted type **Overall Length:** 3.938 inches **Overall Height:** 1.812 inches **Overall Width:** 1.188 inches **Mounting Hole Diameter:** 0.156 inches and 0.938 inches **Mounting Hole Quantity:** 2 and 2 **Environmental Protection:** Any acceptable **Mounting Hole Style:** 2 bushing mounting w/2 holes **Contact Material:** Phosphor bronze **Contact Surface Treatment:** Silver plated **Fuse Accommodation Quantity:** 2 **Accommodated Fuse Length:** 1.250 inches **Accommodated Ferrule Diameter:** 0.250 inches **Length From Front Protrusion To Mounting Surface:** 0.813 inches **Center To Center Distance Between Outside Mounting Holes Along Width:** 0.969 inches **Bushing Hole Diameter:** 0.866 inches **Center To Center Distance Between Bushing Holes:** 0.800 inches Center To Center Distance Between Keyway And Bushing Hole: 0.500 inches **Screw Thread Diameter:** 0.164 inches Screw Thready Qty Per Inch (tpi): 32.0

**Current Carrying Rating In Amps:** 

30.0

## NSN 5920-00-296-2239

Extractor Post Fuseholder - Page 2 of 2



ruse Terminai Type Accommodated:
Ferrule
Voltage In Volts:
250.0
Terminal Type And Quantity:
4 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A014a0