NSN 5920-00-303-5290

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-303-5290 **Body Material:** Plastic **Body Style:** Panel mounted type **Terminal Material:** Copper and brass and phosphor bronze **Terminal Surface Treatment:** Silver plated **Overall Length:** Between 4.609 inches and 4.641 inches **Mounting Hole Diameter:** 0.190 inches **Mounting Hole Quantity: Overall Diameter:** Between 2.359 inches and 2.391 inches **Panel Thickness:** Between 0.109 inches and 0.141 inches **Environmental Protection:** Any acceptable **Mounting Hole Style:** Bushing mounting w/2 holes **Contact Material:** Copper or brass or phosphor bronze **Contact Surface Treatment:** Silver plated **Fuse Accommodation Quantity: Accommodated Fuse Length:** 2.000 inches **Accommodated Ferrule Diameter:** 0.562 inches **Length From Front Protrusion To Mounting Surface:** Between 0.921 inches and 0.953 inches Cap Diameter: Between 1.296 inches and 1.328 inches Center To Center Distance Between Outside Mounting Holes Along Length: Between 1.860 inches and 1.892 inches **Bushing Hole Diameter:** Between 1.108 inches and 1.140 inches **Screw Thread Diameter:**

0.190 inches

NSN 5920-00-303-5290

Extractor Post Fuseholder - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
24.0
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
250.0
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila

A014a0