NSN 5920-00-341-3210

Block Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-341-3210

Body Style:
Open type
Overall Length:
3.844 inches
Overall Height:
2.312 inches
Overall Width:
1.750 inches
Mounting Hole Diameter:
0.190 inches
Mounting Hole Quantity:
2
Base Thickness:
0.500 inches
Mounting Hole Style:
Diagonal to the left
Contact Material:
Beryllium copper
Contact Surface Treatment:
Nickel plated
Fuse Accommodation Quantity:
1
Accommodated Fuse Length:
3.125 inches
Accommodated Ferrule Diameter:
Accommodated Ferrule Diameter: 1.219 inches
1.219 inches
1.219 inches Center To Center Distance Between Fuse Contacts:
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length:
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width:
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.875 inches
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.875 inches Screw Thread Diameter:
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.875 inches Screw Thread Diameter: 0.312 inches
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.875 inches Screw Thread Diameter: 0.312 inches Screw Thready Qty Per Inch (tpi):
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.875 inches Screw Thread Diameter: 0.312 inches Screw Thready Qty Per Inch (tpi): 18.0
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.875 inches Screw Thread Diameter: 0.312 inches Screw Thready Qty Per Inch (tpi): 18.0 Current Carrying Rating In Amps:
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.875 inches Screw Thread Diameter: 0.312 inches Screw Thready Qty Per Inch (tpi): 18.0 Current Carrying Rating In Amps: 600.0
1.219 inches Center To Center Distance Between Fuse Contacts: 2.781 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.875 inches Screw Thread Diameter: 0.312 inches Screw Thready Qty Per Inch (tpi): 18.0 Current Carrying Rating In Amps: 600.0 Internal Circuit Configuration And Pole Quantity:

NSN 5920-00-341-3210

Block Fuseholder - Page 2 of 2



Voltage In Volts:
250.0
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A014a0