

View Online at <https://aerobasegroup.com/nsn/5920-00-422-0550>

**Body Style:**

Panel mounted type

**Overall Length:**

1.156 inches

**Bushing Diameter:**

0.625 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

0.687 inches

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Interruption Indicator Method:**

Incandescent lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

0.518 inches

**Accommodated Fuse Width:**

0.250 inches

**Accommodated Fuse Thickness:**

0.250 inches

**Resistor Rating:**

1.2 kilohms

**Indicating Lamp Voltage Range In Volts:**

+46.0/+60.0

**Length From Front Protrusion To Mounting Surface:**

0.550 inches

**Bushing Thread Length:**

0.312 inches

**Bushing Hole Diameter:**

0.630 inches

**Flatted Side Bushing Hole Length:**

0.573 inches

**Current Carrying Rating In Amps:**

5.0

**Fuse Terminal Type Accommodated:**

Pin

**Voltage In Volts:**

60.0

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Test Data Document:**

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

81349-mil-f-19207/28 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0