

View Online at <https://aerobasegroup.com/nsn/5920-00-422-0550>

Body Style:

Panel mounted type

Overall Length:

1.156 inches

Bushing Diameter:

0.625 inches

Mounting Hole Quantity:

1

Overall Diameter:

0.687 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

0.518 inches

Accommodated Fuse Width:

0.250 inches

Accommodated Fuse Thickness:

0.250 inches

Resistor Rating:

1.2 kilohms

Indicating Lamp Voltage Range In Volts:

+46.0/+60.0

Length From Front Protrusion To Mounting Surface:

0.550 inches

Bushing Thread Length:

0.312 inches

Bushing Hole Diameter:

0.630 inches

Flatted Side Bushing Hole Length:

0.573 inches

Current Carrying Rating In Amps:

5.0

Fuse Terminal Type Accommodated:

Pin

Voltage In Volts:

60.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-f-19207/28 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0