## NSN 5920-00-432-1502

Cartridge Fuse - Page 1 of 1

Fiig: A01700



View Online at https://aerobasegroup.com/nsn/5920-00-432-1502 **Body Style:** Tube type **Terminal Surface Treatment:** Nickel **Overall Length:** 1.250 inches **Overall Diameter:** 0.250 inches **Continuous Current Rating In Amps:** 5.000 **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Opaque body **Features Provided:** Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 200 pct of current rating and 300.0 200 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 10000.0 **Test Data Document:** 81349-mil-f-23419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-f-23419/3 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** No