## NSN 5920-00-443-4081

Block Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-443-4081

## **Body Material:**

Plastic, diallyl phthalate, mil-m-14, type mdg and plastic, diallyl phthalate, mil-m-14, type sdg and plastic, melamine, mil-m-14, type mme and plastic, silicone, mil-m-14, type msg

**Body Style:** 

Clip connected type

**Overall Length:** 

Between 2.236 inches and 2.240 inches

**Overall Height:** 

Between 0.680 inches and 0.720 inches

**Overall Width:** 

Between 4.390 inches and 4.430 inches

**Mounting Hole Diameter:** 

0.138 inches

**Mounting Hole Quantity:** 

4

**Base Thickness:** 

Between 0.230 inches and 0.270 inches

**Mounting Hole Style:** 

One hole mounting

**Contact Material:** 

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

**Contact Surface Treatment:** 

Copper and tin plated and zinc plated

**Fuse Accommodation Quantity:** 

5

**Accommodated Fuse Length:** 

1.250 inches

**Accommodated Ferrule Diameter:** 

0.250 inches

**Current Carrying Rating In Amps:** 

30.0

**Internal Circuit Configuration And Pole Quantity:** 

5 pole, mainline, fused

**Fuse Terminal Type Accommodated:** 

Ferrule

Voltage In Volts:

250.0

**Test Data Document:** 

81349-mil-f-21346 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

10 screw

Shelf Life:

. . . .

## NSN 5920-00-443-4081

Block Fuseholder - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A014a0