

View Online at <https://aerobasegroup.com/nsn/5920-00-470-2514>

Body Style:

Panel mounted type

Overall Length:

Between 3.750 inches and 4.000 inches

Overall Height:

Between 1.796 inches and 1.828 inches

Overall Width:

Between 1.174 inches and 1.204 inches

Mounting Hole Diameter:

0.156 inches

Mounting Hole Quantity:

2

Environmental Protection:

Shock proof

Mounting Hole Style:

2 bushing mounting w/2 holes

Lens Color:

Clear

Contact Material:

Copper

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

120.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+250.0

Length From Front Protrusion To Mounting Surface:

0.812 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.974 inches

Bushing Hole Diameter:

0.875 inches

Center To Center Distance Between Bushing Holes:

0.926 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.469 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0