

View Online at <https://aerobasegroup.com/nsn/5920-00-477-6451>

Body Style:

Rear panel mounted type

Overall Length:

4.203 inches

Overall Height:

1.375 inches

Overall Width:

1.375 inches

Mounting Hole Diameter:

0.166 inches

Mounting Hole Quantity:

4

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting w/4 holes

Lens Color:

Clear

Contact Material:

Copper alloy

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Resistor Rating:

200.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+250.0

Length From Front Protrusion To Mounting Surface:

0.812 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

1.688 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

1.688 inches

Bushing Hole Diameter:

1.156 inches

Center To Center Distance Between Bushing Hole And Mounting Hole:

0.844 inches

Screw Thread Diameter:

0.138 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

500.0

Terminal Type And Quantity:

2 threaded stud

Reference Number Differentiating Characteristics:

As differentiated by navord od41152

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0