

View Online at <https://aerobasegroup.com/nsn/5920-00-477-6451>

**Body Style:**

Rear panel mounted type

**Overall Length:**

4.203 inches

**Overall Height:**

1.375 inches

**Overall Width:**

1.375 inches

**Mounting Hole Diameter:**

0.166 inches

**Mounting Hole Quantity:**

4

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting w/4 holes

**Lens Color:**

Clear

**Contact Material:**

Copper alloy

**Contact Surface Treatment:**

Silver plated

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.500 inches

**Accommodated Ferrule Diameter:**

0.406 inches

**Resistor Rating:**

200.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+90.0/+250.0

**Length From Front Protrusion To Mounting Surface:**

0.812 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

1.688 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

1.688 inches

**Bushing Hole Diameter:**

1.156 inches

**Center To Center Distance Between Bushing Hole And Mounting Hole:**

0.844 inches

**Screw Thread Diameter:**

0.138 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

500.0

**Terminal Type And Quantity:**

2 threaded stud

**Reference Number Differentiating Characteristics:**

As differentiated by navord od41152

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0