

View Online at <https://aerobasegroup.com/nsn/5920-00-481-8945>

Body Material:

Plastic, phenolic, mil-m-14, type cfg

Body Style:

Bushing mounted type

Terminal Material:

Brass

Terminal Surface Treatment:

Electrotinned

Overall Length:

2.375 inches

Bushing Diameter:

0.625 inches

Mounting Hole Quantity:

1

Overall Diameter:

0.940 inches

Environmental Protection:

Any acceptable

Mounting Hole Style:

Bushing mounting

Lens Color:

Clear

Contact Material:

Beryllium copper

Contact Surface Treatment:

Nickel plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

27.0 kilohms

Indicating Lamp Voltage Range In Volts:

+100.0/+125.0

Length From Front Protrusion To Mounting Surface:

0.812 inches

Bushing Thread Length:

0.500 inches

Cap Diameter:

0.938 inches

Bushing Hole Diameter:

Between 0.627 inches and 0.635 inches

Flatted Side Bushing Hole Length:

Between 0.567 inches and 0.575 inches

Current Carrying Rating In Amps:

20.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

125.0

Special Features:

Pilot light application; indicator light is off when fuse is blown

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0