

View Online at <https://aerobasegroup.com/nsn/5920-00-487-4256>

Body Style:

Bushing mounted type

Overall Length:

3.281 inches

Bushing Diameter:

0.625 inches

Overall Width:

0.813 inches

Body Diameter:

0.813 inches

Environmental Protection:

Dripproof and fungus proof and salt spray

Mounting Hole Style:

Bushing mounting

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

1.2 kilohms

Indicating Lamp Voltage Range In Volts:

+45.0/+60.0

Length From Front Protrusion To Mounting Surface:

1.190 inches

Bushing Thread Length:

0.440 inches

Cap Diameter:

0.438 inches

Bushing Hole Diameter:

0.631 inches

Flatted Side Bushing Hole Length:

0.590 inches

Current Carrying Rating In Amps:

20.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

60.0

Terminal Type And Quantity:

2 tab, solder lug

Reference Number Differentiating Characteristics:

As differentiated by navord od 41152

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0