

View Online at <https://aerobasegroup.com/nsn/5920-00-493-8307>

Body Style:

Bushing mounted type

Overall Length:

3.310 inches

Bushing Diameter:

0.625 inches

Overall Width:

0.820 inches

Body Diameter:

0.820 inches

Mounting Hole Quantity:

1

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Indicating Lamp Voltage Range In Volts:

+2.5/+4.0

Length From Front Protrusion To Mounting Surface:

1.190 inches

Bushing Thread Length:

0.440 inches

Cap Diameter:

0.530 inches

Bushing Hole Diameter:

0.630 inches

Flatted Side Bushing Hole Length:

0.573 inches

Current Carrying Rating In Amps:

20.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

4.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-f-19207/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0