NSN 5920-00-504-0540

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-504-0540

view Offilite at https://aerobasegroup.com/histi/3320-00-304-0340
Body Style:
Tube type
Terminal Material:
Brass or copper or copper alloy
Terminal Surface Treatment:
Silver plated
Overall Length:
1.250 inches
Overall Diameter:
0.250 inches
Case Material:
Ceramic or plastic
Continuous Current Rating In Amps:
5.000
Maximum Voltage Rating In Volts:
125.0 ac and 125.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
12.0 200 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
10000.0
Precious Material And Location:
Terminal surfaces silver
Precious Material:
Silver
Test Data Document:
81349-mil-prf-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-15160/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A01700

NSN 5920-00-504-0540Cartridge Fuse - Page 2 of 2



Mil-std (military Standard):

Mil-prf-15160 spec.